我们的目标:

我们将致力于与中高端品牌进行专业OEM 和ODM商务合作。在专业清洁设备的设计和制造上,成为客户首选!

Our Mission:

Striving to be a professional and reliable OEM & ODM partner for medium and high end brands!

我们的愿景:

我们将为客户提供**高效、可靠和智能的清洁**产品, 致力于改变人们的生活品质!

Our Vision:

We deliver Effective, Reliable and Intelligent Cleaning products to our customers, striving to change their life for better and become their first choice!



PROFESSIONAL MANUFACTURER OF CLEANING EQUIPMENT

Floor cleaning machine/sweeping machine/cleaning machine

专业清洁设备供应商

PROFESSIONAL SUPPLIER OF CLEANING EQUIPMENT

洗地机/扫地机/清洗机




Walk-behind series Cleaning machine



适用场所:

酒店、超市、医院、办公场所、车站、机场、大型停车场、 工厂、港口等。

实用应用/Practical use











Application places:

Walk-behind series Cleaning machine

E100产品特点及优势

- ·E100迷你自动洗地机,宽度45CM,尺寸小巧,可清洗普通清洁机械难以处理的区域, 地面清洗抛光、吸水、一机多能;
- ·人性化设计,智能操作面板一键启动;
- · 刷盘转速/清洁水量三档可调, 应对不同清洁场景;
- ·标配磁吸刷盘/百洁垫,装刷卸刷简单快捷;
- ·倾斜式机身设计,方便注水和排污;
- ·配备刷盘+吸力 双无刷电机, 能耗更低,效率更高,寿命更 consumption, higher efficiency and longer service life;

 · The standard lithium battery can be used for 90 mir
- ·标配锂电池一次充电可使用90分钟,清洁效率高达 1000**㎡**/小时.

Advantages

- E100 mini automatic floor washer, 45cm wide and small in size, can clean areas that are difficult to be handled by ordinary cleaning machines, and can clean and polish the ground, absorb water, and have multiple functions;
- · Humanized design, intelligent operation panel starts with one button;
- \cdot The rotating speed of brush disc/cleaning water volume can be adjusted in three gears to cope with different cleaning scenarios;
- · Standard magnetic brush suction plate/cleaning pad, easy and quick to install and remove brush;
- · Inclined fuselage design, convenient for water injection and sewage discharge:
- · Equipped with brush disc+suction double brushless motor, lower energy consumption, higher efficiency and longer service life;
- \cdot The standard lithium battery can be used for 90 minutes at a time, and the cleaning efficiency is up to 1000 ${\it m}^{\prime}/h$
- Patented design for brush adapter, which can realize automatic loading and unloading of brush plates, longer lifetime.

技术参数 /Technical specifications

| Technical Spec/技术参数 | Unit/单位 | E100 |
|--------------------------------------|---------|--------------|
| Clean productivity theoretical工作效率理论 | m²/h | 800/1000 |
| Scrubbing width刮水宽度 | mm | 450 |
| Washing width洗地宽度 | mm | 430 |
| Max. speed最大速度 | Km/h | - |
| Solution tank capacity清水箱容积 | L | 4 |
| Recovery tank capacity污水箱容积 | L | 6.5 |
| Voltage工作电压 | V | 36 |
| Brush motor rated power刷盘电机功率 | W | 150*2 |
| Vacuum motor rated power吸水电机功率 | W | 150 |
| Drive motor rated power驱动电机功率 | W | - |
| Brush/Pad diameter刷盘/针盘直径 | mm | 215*2 |
| Brush speed刷盘转速 | Rpm | 0-350 |
| Brush pressure刷盘压力 | Кд | 6 |
| Vacuum power吸力 | Kpa | 11 |
| Sound level at 1.5m工作噪音 | dB(A) | 60 |
| Battery compartment size(LxWxH)电池仓尺寸 | mm | - |
| Recommend battery capacity 标配电池容量 | V/Ah | 36V8Ah |
| Gross weight毛重(含电池) | Кв | 26 |
| Machine size(LxWxH)整机尺寸 | mm | 1155×525×380 |

Walk-behind series Cleaning machine

E380C








适用场所:

酒店、超市、医院、办公场所、车站、机场、大型停车场、工厂、港口等。

实用应用/Practical use













Application places:

Walk-behind series Cleaning machine

E380C产品特点及优势

E380C小型手推式洗地机配备双无刷电机,效率高,寿命长,维护成本低;

- ·最新能耗控制系统搭配锂电池,一次充电可使用1-2个小时;
- ·造型小巧, 洗地宽度380mm,方便进入狭窄区域工作;
- ·一体式铸造吸水趴,坚固防锈,胶条更换简单;
- · 挡水裙边有效防止污水飞溅,控制清洁区域;
- · 可折叠设计,占用空间更小;
- ·智能操控手柄,一键启动,水量多档可调,人性化设置方便操作.

Advantages

E380C small hand-push floor washer is equipped with double brushless motors, which has high efficiency, long service life and low maintenance cost;


- · The latest energy consumption control system is equipped with lithium battery, which can be used for 1-2 hours at a time;
- · Compact shape, 380mm wide floor washing, easy to work in narrow areas;
- · One-piece casting water absorption, solid and rust-proof, and easy replacement of rubber strips;
- · The water retaining skirt can effectively prevent sewage splashing and control the clean area;
- · Foldable design, occupying less space;
- · Intelligent control handle, one-button start, water volume adjustable in multiple gears, user-friendly setting and convenient operation
- Patented design for brush adapter, which can realize automatic loading and unloading of brush plates, longer lifetime.

技术参数 /Technical specifications

| Technical Spec/技术参数 | Unit/单位 | E380C |
|--------------------------------------|---------|-------------|
| Clean productivity theoretical工作效率理论 | m²/h | 1000/1200 |
| Scrubbing width刮水宽度 | mm | 420 |
| Washing width洗地宽度 | mm | 380 |
| Max. speed最大速度 | Km/h | - |
| Solution tank capacity清水箱容积 | L | 20 |
| Recovery tank capacity污水箱容积 | L | 18 |
| Voltage工作电压 | V | 24 |
| Brush motor rated power刷盘电机功率 | W | 400 |
| Vacuum motor rated power吸水电机功率 | W | 380 |
| Drive motor rated power驱动电机功率 | W | = |
| Brush/Pad diameter刷盘/针盘直径 | mm | 380 |
| Brush speed刷盘转速 | Rpm | - |
| Brush pressure刷盘压力 | Кв | 8 |
| Vacuum power吸力 | Кра | 11 |
| Sound level at 1.5m工作噪音 | dB(A) | 55 |
| Battery compartment size(LxWxH)电池仓尺寸 | mm | 285*165*230 |
| Recommend battery capacity 标配电池容量 | V/Ah | 24V32Ah |
| Gross weight毛重(含电池) | Kg | 50 |
| Machine size(LxWxH)整机尺寸 | mm | 800x440x980 |

Walk-behind series Cleaning machine

E531B/D



全铝压铸喷涂刷盘 罩,坚固耐用



根据不同需求调节 行走速度




一键启动轻松释放 刷盘/针盘



适用场所:

酒店、超市、医院、办公场所、车站、机场、大型停车场、工厂、港口等。

实用应用/Practical use











Application places:

Walk-behind series Cleaning machine

E531B/D产品特点及优势

- ·污水箱大开口,可翻转、免工具拆卸设计,易清洁维护;
- ·按键式操作面板,操作简单可靠,维护成本低;
- · 前置大注水口, 加水方便快捷;
- ·全铝压铸,喷涂工艺处理刷盘罩及水刮架,坚固耐用,不 · Large water inlet in front of solution tank, easy and quick to add 生锈;
- ·专利刷盘对地压力可调节结构设计,可轻松应对不同清洁 surface coating, which is durable and antirust; 要求地面,高效可靠;
- · 高效机械降噪系统,可有效的降低工作时设备噪音;
- ·高效可靠的机械消泡及污水箱水满报警机构,大大提升吸 the machine sound level during work; 力电机使用寿命;
- · 整机采用双无刷电机, 电机控制器集数字化过流、欠压保 motor; 护功能;
- ·高效无刷电机定制机型,寿命更长久,品质更可靠,一次 undervoltage protection functions; 充电可实现4~6小时连续工作;
- · 专利刷盘卡口设计,可实现刷盘自动装卸,卡口使用寿命 更长久。

Advantages

- · Large opening of recovery tank, reversible and tool free disassembly design for recovery tank cover, easy to clean and maintain:
- · Touch switch operation panel, simple and reliable operation, low maintenance cost;
- water;
- · Aluminum die-casting brush deck and squeegee frame with
- · The patented brush system is designed for brush pressure adjustment, and it's easily cope with different floor cleaning requirements, efficient and reliable;
- · Efficient noise reduction system, which can effectively reduce
- · Efficient and reliable mechanical defoaming system and waterfull alarm of recovery tank, greatly improving the lifetime of vacuum
- · Soft start design for both brushless brush motor and brushless vacuum motor, the controller has digital overcurrent and
- · High efficiency brushless motor customized model with longer lifetime, more reliable quality, and one full battery charge can keep machine working 4-6 hours;
- Patented design for brush adapter, which can realize automatic loading and unloading of brush plates, longer lifetime.

技术参数 /Technical specifications

| Technical Spec/技术参数 | Unit/单位 | E531B | E531BD |
|--------------------------------------|---------|---------------|---------------|
| Clean productivity theoretical工作效率理论 | m²/h | 2200/1800 | 2650/2100 |
| Scrubbing width刮水宽度 | mm | 780 | 780 |
| Washing width洗地宽度 | mm | 530 | 530 |
| Max. speed最大速度 | Km/h | - | 5.0 |
| Solution tank capacity清水箱容积 | L | 50 | 50 |
| Recovery tank capacity污水箱容积 | L | 45 | 45 |
| Voltage工作电压 | V | 24 | 24 |
| Brush motor rated power刷盘电机功率 | W | 450 | 480 |
| Vacuum motor rated power吸水电机功率 | W | 250 | 400 |
| Drive motor rated power驱动电机功率 | W | - | 150 |
| Brush/Pad diameter刷盘/针盘直径 | mm | 530 | 530 |
| Brush speed刷盘转速 | Rpm | 153 | 153 |
| Brush pressure刷盘压力 | Кд | 21/28 | 21/28 |
| Vacuum power吸力 | Kpa | >12.5 | >12.5 |
| Sound level at 1.5m工作噪音 | dB(A) | <68 | <68 |
| Battery compartment size(LxWxH)电池仓尺寸 | mm | 340*340*230 | 340*340*230 |
| Recommend battery capacity 标配电池容量 | V/Ah | 2*12V100Ah | 2*12V100Ah |
| Gross weight毛重(含电池) | Кд | 160 | 189 |
| Machine size(LxWxH)整机尺寸 | mm | 1220x540x1058 | 1220×540×1058 |

Ride on series Cleaning machine

E531R












适用场所:

酒店、超市、医院、办公场所、车站、机场、大型停车场、 工厂、港口等。

实用应用/Practical use











Application places:

Ride on series Cleaning machine

E531R产品特点

- · E531R是一款全新自主设计的小型迷你驾驶式洗地机,标配20寸单刷,70升大容量清水箱、污水箱,
- ·前置注水口,整车尺寸设计小巧,外加采用前驱式无底盘 专利设计;
- ·整车重量轻、转弯半径小、操控灵活,方便电梯进出,非常适合小通道及多楼层间操作;
- · 整机集成防水触控式面板设计,操作简单便捷;
- ·标配液晶显示屏,可视化设备参数,读取方便,故障维修简单快捷;
- ·清洁水量及行驶速度三档可调节设计,内置一键ECO超静音节能功能,适用于声音敏感环境;
- · 创新式刷盘和水刮架双电动推杆设计,刷盘、水刮架一键电动升降,倒车水刮架自动抬升,安全高效;
- ·铝合金压铸刷盘罩及吸水扒,刷盘内置一键自动装、卸;
- · 污水箱大开口, 可翻转、免工具拆卸设计, 易清洁维护;
- ·配备座椅安全开关,驾驶员离座自动停机,操作更加安全可靠;
- · 专利刷盘卡口设计,可实现刷盘自动装卸,卡口使用寿命 更长久。

E531R Product Highlights

- E531R is a new designed Mini ride on floor washing machine with compact size. Single brush of 20 inches, 70L capacity both for solution tank and recovery tank.
- · Patented frame-less chassis design with front drive wheel.
- · Light weight, small turning radius and flexible operation, it is very suitable for small passageway and multi-floor operation. · The whole machine integrated waterproof touch panel design, easy to operate; LCD display, visual equipment parameters, easy to read and fast maintenance:
- · 3 adjustable grades design for clean water volume and drive speed, built-in one-button ECO model, suitable for sound sensitive environment;
- · Innovative double electric push rod design for brush and squeegee system, one-key automatic lifting of brush and squeegee system, automatic lifting when machine back off, safe and efficient;
- · Aluminum die-casting brush deck and squeegee assembly, automatic brush loading and unloading built-in one-button;
- · Large opening of recovery tank, reversible and tool free disassembly design for recovery tank cover, easy to clean and maintain;
- \cdot Seat with safety switch equip on the machine, when driver leave machine will automatically stop, more safe and reliable operation.
- \cdot Patented design for brush adapter, which can realize automatic loading and unloading of brush plates, longer lifetime.

技术参数 /Technical specifications

| Technical Spec/技术参数 | Unit/单位 | E531R |
|--------------------------------------|---------|---------------|
| Clean productivity theoretical工作效率理论 | m²/h | 3450/2750 |
| Scrubbing width刮水宽度 | mm | 780 |
| Washing width洗地宽度 | mm | 530 |
| Max. speed最大速度 | Km/h | 6.5 |
| Solution tank capacity清水箱容积 | L | 70 |
| Recovery tank capacity污水箱容积 | L | 70 |
| Voltage工作电压 | V | 24 |
| Brush motor rated power刷盘电机功率 | W | 550 |
| Vacuum motor rated power吸水电机功率 | W | 400 |
| Drive motor rated power驱动电机功率 | W | 550 |
| Brush/Pad diameter刷盘/针盘直径 | mm | 530 |
| Brush speed刷盘转速 | Rpm | 180 |
| Brush pressure刷盘压力 | Кд | 35 |
| Vacuum power吸力 | Kpa | 12.5 |
| Sound level at 1.5m工作噪音 | dB(A) | <68 |
| Battery compartment size(LxWxH)电池仓尺寸 | mm | 420*340*260 |
| Recommend battery capacity 标配电池容量 | V/Ah | 2*12V120Ah |
| Gross weight毛重(含电池) | Кд | 200 |
| Machine size(LxWxH)整机尺寸 | mm | 1220x540x1010 |

Ride on series Cleaning machine

E810R














适用场所:

酒店、超市、医院、办公场所、车站、机场、大型停车场、 工厂、港口等。

实用应用/Practical use









Hotel, supermarket, hospital, office, station, airport, large parking lot,

Application places:

factory, port and the like.



Ride on series Cleaning machine

E810R产品特点

E810R是一款全新自主设计的中型前轮驱动型驾驶式双刷洗地机,机器标配2个16寸刷盘,整车尺寸设计紧凑、稳固,底盘采用中央隧道式专利设计,低重心、转弯半径小、操控灵活安全,非常便于操作;

- · 120L大容量清水箱和污水箱分割采用低电池仓和低污水箱重心分割设计,电池安装和整机检修安全快捷;
- ·集成防水触控式面板设计,操作简单便捷;
- · 标配液晶显示屏,可视化设备参数,读取方便,故障维修简单快捷;
- ·清洁水量及行驶速度三档可调节设计,内置一键ECO超静音节能功能,适用于声音敏感环境;
- ·集成式24V五合一电控系统,内设电机过流及电池低电压保护功能,刷盘、水刮架一键电动升降,倒车水刮架自动抬升,安全高效;
- · 专利刷盘卡口设计,可实现刷盘自动装卸,卡口使用寿命 更长久;
- ·污水箱大开口,可翻转、免工具拆卸设计,易清洁维护;
- ·配备污水箱液位传感器,污水箱满自动停机,更好地保护 吸水电机,延长使用寿命;
- · 配备座椅安全开关,驾驶员离座自动停机,操作更加安全可靠。

E810R Product Highlights

- E810R is a new designed medium size ride on floor washing machine with 2*15 inch brushes. Patented central tunnel design chassis design with front drive wheel. Underslung design, small turning radius and flexible operation, it is very suitable for operation.
- 120L large capacity solution tank and recovery tank is divided by low battery compartment and low recovery tank center of gravity division design, safe and fast operation both for battery installation and machine maintenance.
- \cdot The whole machine integrated waterproof touch panel design, easy to operate;
- \cdot LCD display, visual equipment parameters, easy to read and fast maintenance;
- \cdot There are 3 adjustable grades design for clean water volume and drive speed;
- · Double electric push rod design for brush and squeegee system, one-key automatic lifting of brush and squeegee system, automatic lifting when machine back off, safe and efficient;
- \cdot Magnetic type brush /pad connection mode, easy and convenient for brush/pad installation and uninstallation;
- · Large opening of recovery tank, reversible and tool –free disassembly design for recovery tank cover, easy to clean and maintain:
- · Seat safety switch equip on the machine, when driver leave machine will automatically stop, more safe and reliable operation.

技术参数 /Technical specifications

| Technical Spec/技术参数 | Unit/单位 | E810R | |
|--------------------------------------|---------|---------------|--|
| Clean productivity theoretical工作效率理论 | m²/h | 5200/4200 | |
| Scrubbing width刮水宽度 | mm | 1060 | |
| Washing width洗地宽度 | mm | 810 | |
| Max. speed最大速度 | Km/h | 6.5 | |
| Solution tank capacity清水箱容积 | L | 120 | |
| Recovery tank capacity污水箱容积 | L | 120 | |
| Voltage工作电压 | V | 24 | |
| Brush motor rated power刷盘电机功率 | W | 380*2 | |
| Vacuum motor rated power吸水电机功率 | W | 500 | |
| Drive motor rated power驱动电机功率 | W | 650 | |
| Brush/Pad diameter刷盘/针盘直径 | mm | 410*2 | |
| Brush speed刷盘转速 | Rpm | 200 | |
| Brush pressure刷盘压力 | Kg | 45 | |
| Vacuum power吸力 | Kpa | >15 | |
| Sound level at 1.5m工作噪音 | dB(A) | <70 | |
| Battery compartment size(LxWxH)电池仓尺寸 | mm | 450*450*298 | |
| Recommend battery capacity 标配电池容量 | V/Ah | 4*6V200Ah | |
| Gross weight毛重(含电池) | Кд | 320 | |
| Machine size(LxWxH)整机尺寸 | mm | 1415*865*1120 | |

Ride on series Cleaning machine

E1060R E860R Pro MAX











适用场所:

酒店、超市、医院、办公场所、车站、机场、大型停车场、 工厂、港口等。

实用应用/Practical use









Hotel, supermarket, hospital, office, station, airport, large parking lot,

Application places:

factory, port and the like.



Ride on series Cleaning machine

E1060R/E860R Pro MAX产品特点

此机型是一款全新设计中大型前轮驱动驾驶式双刷洗地 This model is a new large size front-wheel drive ride on floor 机,机器最大可配备2个20寸刷盘,200L清水箱/210L污水 箱容积,整机设计可标配36V200Ah铅酸电池或锂电池。

- · 整机采用模块化和紧凑化设计理念,确保机器参数足够大 的前提下依然拥有充分的灵活性和操控性能;
- ·水箱采用低电池仓和低污水箱重心分割设计理念,电池安 装和整机检修安全快捷;
- · 集成防水触控式电子面板设计,清洁水量及行驶速度三档 可调节设计,操作简单便捷、易学;
- · 标配大尺寸彩色高清液晶显示屏, 可视化设备参数, 读取 方便,故障维修简单快捷;
- · 标配清水箱/污水箱电子液位显示器, 水位显示直观方便, 污水箱满自动报警停机;
- ·整机电机一键式软启动设计,控制器集数字化过流、欠压 · Soft start design for both brush motor and vacuum motor, the 保护以及故障检测功能;
- · 专利刷盘卡口设计,可实现刷盘自动装卸,卡口使用寿命 更长久;
- ·一键ECO超静音节能功能,适用于声音敏感环境;
- ·采用36V高电压低电流供电系统,一次充电可实现6~7小 时超长连续工作时间。

E1060R/E860R Pro MAX Advantages

washing machine, with 200L solution tank/210L recovery tank capacity, machine standard equip with 36V200Ah DC AGM battery or Lithium battery.

- modular and compact design concept to ensure that the machine parameters are large enough while still having full flexibility and driving performance.
- · Low battery compartment and low recovery tank center of gravity division design, safe and fast operation both for battery installation and machine maintenance.
- Integrated waterproof touch electronic panel design, clean water and speed three adjustable design, easy to operate, easy to
- · HD LCD screen, visual equipment parameters, easy to read, simple and fast fault maintenance;
- · Electronic liquid level display for solution tank/recovery tank water, intuitive and convenient display of cleaning water volume, automatic alarm and stop when the recovery tank is full;
- controller integrates digital overcurrent, undervoltage protection and fault detection functions
- · Patented design for brush adapter, which can realize automatic loading and unloading of brush plates, longer lifetime;;
- · ECO model with lower sound and power consumption, suitable for sound sensitive environment;
- 36V DC power supply system, one full battery charge can achieve 6~7 hours of continuous running

技术参数 /Technical specifications

| Technical Spec/技术参数 | Unit/单位 | E860R Pro MAX | E1060R |
|---|---------|-------------------|----------------|
| Clean productivity theoretical/Actual工作效率理论 | m²/h | 5590/4490 | 6800/5500 |
| Scrubbing width刮水宽度 | mm | 1060 | 1200 |
| Washing width洗地宽度 | mm | 860 | 1060 |
| Max. speed最大速度 | Km/h | 6.5 | 6.5 |
| Solution tank capacity清水箱容积 | L | 200 | 200 |
| Recovery tank capacity污水箱容积 | L | 210 | 210 |
| Voltage工作电压 | v | 36 | 36 |
| Brush motor rated power刷盘电机功率 | W | 550*2 | 550*2 |
| Vacuum motor rated power吸水电机功率 | W | 600 | 600 |
| Drive motor rated power驱动电机功率 | W | 650 | 800 |
| Brush/Pad diameter刷盘/针盘直径 | mm | 430*2 | 530*2 |
| Brush speed刷盘转速 | Rpm | 180 | 180 |
| Brush pressure刷盘压力 | Kg | 55 | 60 |
| Vacuum power吸力 | Kpa | 17 | 17 |
| Sound level at 1.5m工作噪音 | dB(A) | <68 | <68 |
| Battery compartment size(LxWxH)电池仓尺寸 | mm | 545*545*310 | 545*545*310 |
| Recommend battery capacity 标配电池容量 | V/Ah | 3*12V/150Ah | 6*6V/200Ah |
| Gross weight毛重(含电池) | Kg | 415 | 477 |
| Machine size(LxWxH)整机尺寸 | mm | 1730 × 910 × 1350 | 1730910 × 1350 |

Walk-behind series Cleaning machine


EC530B/D



适用场所:

酒店、超市、医院、办公场所、车站、机场、大型停车场、工厂、港口等。

实用应用/Practical use











Application places:

Walk-behind series Cleaning machine

EC530B/D产品特点及优势

EC530B/D是一款全新自主设计的小型手推式洗地机, 前置大注水口,加水方便快捷;

- ·全铝压铸,喷涂工艺处理刷盘罩及水刮架,坚固耐用,不生锈;
- · 整机集成防水触控式面板设计,操作简单便捷;
- · 标配液晶显示屏,可视化设备参数,读取方便,故障维修简单快捷;
- · 高效可靠的机械消泡及污水箱水满报警机构,大大提升吸力电机使用寿命;
- · 专利刷盘卡口设计,可实现刷盘自动装卸,卡口使用寿命 更长久。

Advantages

EC530B/D is a new self-designed small hand-push floor washer, with a large water injection nozzle in front, which is convenient and quick to add water;

- · All-aluminum die-casting, spray processing brush cover and water scraper frame, durable and rust-free;
- The integrated waterproof touch panel design of the whole machine makes the operation simple and convenient;
- · Standard LCD display screen, visualizing equipment parameters, easy to read, simple and fast fault maintenance;
- \cdot Efficient and reliable mechanical defoaming and sewage tank full alarm mechanism, greatly improving the service life of suction motor;
- \cdot The patented brush disc bayonet design can realize automatic loading and unloading of the brush disc, and the service life of the bayonet is longer.

技术参数 /Technical specifications

| Technical Spec/技术参数 | Unit/单位 | EC530B | EC530D |
|--------------------------------------|---------|---------------|---------------|
| Clean productivity theoretical工作效率理论 | m²/h | 2200/1800 | 2650/2100 |
| Scrubbing width刮水宽度 | mm | 830 | 830 |
| Washing width洗地宽度 | mm | 530 | 530 |
| Max. speed最大速度 | Km/h | - | 5.0 |
| Solution tank capacity清水箱容积 | L | 50 | 50 |
| Recovery tank capacity污水箱容积 | L | 55 | 55 |
| Voltage工作电压 | V | 24 | 24 |
| Brush motor rated power刷盘电机功率 | W | 550 | 550 |
| Vacuum motor rated power吸水电机功率 | W | 400 | 400 |
| Drive motor rated power驱动电机功率 | W | - | 150 |
| Brush/Pad diameter刷盘/针盘直径 | mm | 530 | 530 |
| Brush speed刷盘转速 | Rpm | 153 | 153 |
| Brush pressure刷盘压力 | Кд | 21/28 | 21/28 |
| Vacuum power吸力 | Kpa | >12.5 | >12.5 |
| Sound level at 1.5m工作噪音 | dB(A) | <68 | <68 |
| Battery compartment size(LxWxH)电池仓尺寸 | mm | 340*340*230 | 340*340*230 |
| Recommend battery capacity 标配电池容量 | V/Ah | 2*12V100Ah | 2*12V100Ah |
| Gross weight毛重(含电池) | Кд | 160 | 189 |
| Machine size(LxWxH)整机尺寸 | mm | 1220x540x1058 | 1220×540×1058 |